

Surveillance Series

High Definition Network Camera

GND1110P

Key Feature

- High Definition video Resolution of 1280x720
- Wide angle 3.6mm Fixed Lens
- 15M IR Distance night vision
- Compact Sized Dome



Specifications

VIDEO	
Imaging Device	1/4" 1.0 Megapixel Progressive CMOS Sensor
Video Frame Rate	1280x720@30fps
Min. Illumination	Color: 0.3 Lux@F1.2, B/W:0.08Lux@F1.2, IR On: 0Lux@F1.2
Mechanical IR Cut (ICR)	Automatically Switches
IR Distance	15M
LENS	
Focal Length	F3.6mm
Lens Adapter	Fixed Lens
Mount Type	On Board
Min. Object Distance	0.3m
Lens Type	DC auto iris
OPERATIONAL	
On Screen Display	English / Traditional Chinese / Simplified Chinese / Japanese / French / Russian / Portuguese / German / Spanish / Polish / Danish
Day & Night	Color / B&W / Auto
Motion Detection	On: Area Program/Off
Privacy Masking	On: Area Program/Off
Image Setting	Brightness / Contrast / Sharpness
White Balance	ATW / AWB
Electronic Shutter Speed	1/2~1/2000s
NETWORK	
Ethernet	RJ-45 (10/100/M)
Video Compression Format	H.264, MPEG4, M-JPEG Streaming
Bit Rate	64 up to 6,000 Kbps
Protocol	TCP/IP, HTTP, HTTPS, SMTP, FTP, NTP, DNS, DHCP, PPPoE, IGMP, UPnP, RTSP, RTP, RTCP, SNMP, Ethernet (RJ45 10/100M)
Alarm Trigger	FTP and Email, HTTP
Audio Boardcast	N/A
Web Viewer	Microsoft Internet Explorer * Windows only
ENVIRONMENTAL	
Operating Temperature	0°C~40°C
Operating Humidity	Less than 80% RH
Protection Level	N/A
ELECTRICAL	
Input Voltage	12V DC
Power Consumption	4W, IR On:6W
MECHANICAL	
Connector	RJ45, DC Power
Dimensions	ø69x94(H)mm
Net Weight	350g

* Derivative products : GND-1110P

Deutsch Sicherheit Standard
Security Camera
Network Dome Camera

D.S.S.
Technik Für Sicherheit