



Surveillance Series

High Resolution AHD Camera

GHB2550P

Key Feature

- Hybrid Analog and AHD System Camera
- High Quality video Resolution of 2 Megapixel
- 3.0- 10.5mm Fixed Lens
- Control Over Coaxial (CoC Function)
- 25M IR Distance
- Transmission distance compensation



Specifications

VIDEO	
Imaging Device	1/3" SONY 2.1 Megapixel Progressive CMOS Sensor
Video Resolution	Analog : 700TVLine ; AHD : 1920x1080
Min. Illumination	Color: 0.06 Lux@F1.6, B/W:0.03Lux@F1.6, IR On: 0Lux@F1.6
Mechanical IR Cut (ICR)	Automatically Switches
IR Distance	25M
Encoding System	PAL
LENS	
Focal Length	F3.0-10.5mm
Lens Adapter	Built-in Motorized Lens
Mount Type	On Board
Min. Object Distance	0.2m
Lens Type	DC auto iris
OPERATIONAL	
On Screen Display	English / Traditional Chinese / Simplified Chinese / German
Day & Night	Color / B&W / Auto
WDR ; BLC	D-WDR / WDR / BLC / HLC
Digital Noise Reduction	High / Middle / Low / Off
Motion Detection	On:Sensitivity, Area Program/Off
Privacy Masking	On: Area Program/Off
Image Setting	Brightness / Contrast / Sharpness / Mirror / Flip
White Balance	ATW / AWB / PWB(Push Lock) / Manual
Electronic Shutter Speed	Auto: 1/25~1/50,000s Manual: 1/25~1/50,000s
Operating Video Mode	Analog, AHD (Switchable)
Fog Reduction	N/A
OSD Menu	Control Over Coaxial (CoC)
ENVIRONMENTAL	
Operating Temperature	-10°C~50°C
Operating Humidity	Less than 80% RH
Protection Level	IP66
ELECTRICAL	
Input Voltage	12V DC
Power Consumption	8W
MECHANICAL	
Connector	BNC, DC Power
Dimensions	101.4(W) x 87.3(H) x 280.3(D)mm
Net Weight	640g

* Derivative products : GHB-2550P

Deutsch Sicherheit Standard

Security Camera

AHD Bullet Camera

D.S.S.
Technik Für Sicherheit