

High Resolution AHD IR Dome Camera

DSS-219RHD

D.S.S.

Technik Für Sicherheit

Deutsch Sicherheit Standard
Security Camera

2.4 Mega-Pixel AHD Dome

BNC output

0.001Lux@F1.4

Varifocal 2.8-12mm Lens



Key Feature

- High resolution of 2.4 Megapixel
- 7.0-22mm Varifocal Lens
- 2D/3D Noise Reduction
- Sense Up Function
- PoC Function
- Taiwan Series

Specifications

	DSS-219RHD
VIDEO	
Image Device	1/3" Sony 2.4 Megapixel Progressive Exmor CMOS Sensor
Video Frame Rate	1920x1080P@25/30fps
Min. Illumination	Color:0.05Lux@F1.4, B/W:0.02Lux@F1.4,Sense-up:0.001Lux@F1.4
Video Output	AHD or Composite switchable
IR Distance	N/A
LENS	
Focal Length	F2.8~12mm
Lens Adapter	Built-in Varifocal Lens
Min. Object Distance	0.2m
Lens Type	DC
OPERATIONAL	
OSD Menu	OSD / CoC (Via the coax)
Day&Night	Color / B&W / Auto / IR Sync
Electronic Shutter	Auto :1/25(30)~1/50,000 sec ; Outdoor Max. Shutter Adjustable Manual :1/25(30), 1/50(60), FLK, 1/240, 1/480, 1/1000, 1/2000, 1/5000, 1/10000, 1/50000 sec
White Balance	INDOOR / OUTDOOR / ATW / AWB / AWC / MANUAL
WDR;BLC;HLC	Auto / On / Off ; HSBC: On / Off / LEVEL
Fog Reduction	Auto/Off
Digital Noise Reduction	3DNR / 2DNR
Sense-up	On (x2,x4,x6,x8,x10,x15,x20,x25,x30) /Off
On Screen Display	English, Japanese, Chinese, German, French, Italian, Spanish, Polish, Russian, Portuguese, Dutch, Turkish, Korea, Hebrew, Arabic FREEZE / MIRROR / V-FLIP / ROTATE / NEG.IMAGE
Image Effect	
Privacy Masking	4 Zones Programmable
Motion Detection	On:sensitivity, Off
Lens Shading Compensation	On/Off
ENVIRONMENTAL	
Operation Temp./RH	-10°C~50°C / Less than RH80%
Protection Level.	N/A
ELECTRICAL	
Power Supply	12V DC, 12V DC/24V AC PoC
Power Consumption	1.2W, 2.2W PoC
MECHANICAL	
Dimensions	φ124x102mm
Net weight	320g

* Derivative products : DSS-219RHD

Surveillance Series