

Surveillance Series


High Resolution AHD Camera

GHD2550P

Key Feature

- Hybrid Analog and AHD System Camera
- High Quality video Resolution of 2 Megapixel
- 3.0- 10.5mm Motorized Lens
- Control Over Coaxial (CoC Function)
- Fog Reduction
- Transmission distance compensation

Specifications



VIDEO	
Imaging Device	1/3" SONY 2.2 Megapixel Progressive CMOS Sensor
Video Resolution	Analog : 700TVLine ; AHD : 1920x1080
Min. Illumination	Color: 0.1 Lux@F1.2, B/W:0.06Lux@F1.2
Mechanical IR Cut (ICR)	Automatically Switches
IR Distance	N/A
Encoding System	PAL
LENS	
Focal Length	F3.0-10.5mm
Lens Adapter	Built-in Motorized Lens
Mount Type	On Board
Min. Object Distance	0.2m
Lens Type	DC auto iris
OPERATIONAL	
On Screen Display	English / Traditional Chinese / Simplified Chinese / German
Day & Night	Color / B&W / Auto
WDR ; BLC	D-WDR / WDR / BLC / HLC
Digital Noise Reduction	High / Middle / Low / Off
Motion Detection	On:Sensitivity, Area Program/Off
Privacy Masking	On: Area Program/Off
Image Setting	Brightness / Contrast / Sharpness / Mirror / Flip
White Balance	ATW / AWB / PWB(Push Lock) / Manual
Electronic Shutter Speed	Auto: 1/25~1/50,000s Manual: 1/25~1/50,000s
Operating Video Mode	Analog, AHD (Switchable)
Fog Reduction	Auto / Off
OSD Menu	Control Over Coaxial (CoC)
ENVIRONMENTAL	
Operating Temperature	-10°C~50°C
Operating Humidity	Less than 80% RH
Protection Level	N/A
ELECTRICAL	
Input Voltage	12V DC
Power Consumption	5.5W
MECHANICAL	
Connector	BNC, DC Power
Dimensions	ϕ116 x 95(H)mm
Net Weight	450g

* Derivative products : GHD-2550P

Deutsch Sicherheit Standard

Security Camera

AHD Dome Camera

D.S.S.
Technik Für Sicherheit