

## Surveillance Series

### High Resolution Network Camera

# GND2110P

#### Key Feature

- High Quality video Resolution of 2 Megapixel
- Wide angle 3.6mm Fixed Lens
- 15M IR Distance night vision
- Compact Sized Dome



#### Specifications

<b>VIDEO</b>	
Imaging Device	1/2.9" Sony 2.0 Megapixel Progressive CMOS Sensor
Video Frame Rate	1920x1080@30fps
Min. Illumination	Color: 0.3 Lux@F1.2, B/W:0.08Lux@F1.2, IR On: 0Lux@F1.2
Mechanical IR Cut (ICR)	Automatically Switches
IR Distance	15M
<b>LENS</b>	
Focal Length	F3.6mm
Lens Adapter	Fixed Lens
Mount Type	On Board
Min. Object Distance	0.3m
Lens Type	DC auto iris
<b>OPERATIONAL</b>	
On Screen Display	English / Traditional Chinese / Simplified Chinese / Japanese / French / Russian / Portuguese / German / Spanish / Polish / Danish
Day & Night	Color / B&W / Auto
Motion Detection	On: Area Program/Off
Privacy Masking	On: Area Program/Off
Image Setting	Brightness / Contrast / Sharpness
White Balance	ATW / AWB
Electronic Shutter Speed	1/2~1/2000s
<b>NETWORK</b>	
Ethernet	RJ-45 (10/100/M)
Video Compression Format	H.264, MPEG4, M-JPEG Streaming
Bit Rate	64 up to 6,000 Kbps
Protocol	TCP/IP, HTTP, HTTPS, SMTP, FTP, NTP, DNS, DHCP, PPPoE, IGMP, UPnP, RTSP, RTP, RTCP, SNMP, Ethernet (RJ45 10/100M)
Alarm Trigger	FTP and Email, HTTP
Audio Boardcast	N/A
Web Viewer	Microsoft Internet Explorer * Windows only
<b>ENVIRONMENTAL</b>	
Operating Temperature	0°C~40°C
Operating Humidity	Less than 80% RH
Protection Level	N/A
<b>ELECTRICAL</b>	
Input Voltage	12V DC
Power Consumption	4W, IR On:6W
<b>MECHANICAL</b>	
Connector	RJ45, DC Power
Dimensions	ø69x94(H)mm
Net Weight	350g

\* Derivative products : GND-2110P

**Deutsch Sicherheit Standard**  
Security Camera  
**Network Dome Camera**

**D.S.S.**  
Technik Für Sicherheit