

High Resolution AHD IR Dome Camera

DSS-219RHV

D.S.S.

Technik Für Sicherheit

Deutsch Sicherheit Standard
Security Camera

2.4 Mega-Pixel AHD Dome

BNC output

20m IR Distance

Varifocal 2.8-12mm Lens



Key Feature

- High resolution of 2.4 Megapixel
- 2.8-12mm Varifocal Lens
- Support CoC Function
- IP66 for Outdoor Usage
- PoC Function
- Taiwan Series

Specifications

	DSS-219RHV
VIDEO	
Image Device	1/3" Sony 2.4 Megapixel Progressive Exmor CMOS Sensor
Video Frame Rate	1920X1080p@25/30fps, 1280x720p@30fps
Min. Illumination	Color: 0.05Lux@F1.2, B/W: 0.02Lux@F1.2, IR On: 0Lux@F1.2
Video Output	BNC connector (AHD) & Composite Simultaneous
IR Distance	20m
LENS	
Focal Length	F2.8~12mm
Lens Adapter	Built-in Varifocal Lens
Min. Object Distance	0.2m
Lens Type	DC, D4 IRIS Jack
OPERATIONAL	
OSD Menu	OSD / CoC
Day&Night	Color / B&W / Auto / External
Electronic Shutter	Auto :1/25(30)~1/30, 000 Sec; Flickerless Manual :1/25(30), 1/50(60), 1/100(120), 1/240, 1/500, 1/1000, 1/2000, 1/4000, 1/8000, 1/16000, 1/30000 Sec
White Balance	ATW / AWB / PWB(Push Lock) / Manual
DWDR;BLC;HLC	Level Adjustable ; Program ; On/Off
Fog Reduction	Auto/Manual/Off ; Level: High/Middle/Low
Digital Noise Reduction	HIGH / MIDDLE / LOW / Off
Sense-up	On (x2, x4, x8, x16, x32) / Off
On Screen Display	English, Japanese, Traditional Chinese, Simplified Chinese
E-Zoom	1.0x~8.0x (step 0.1)
Image Effects	Sharpness / Mirror / Flip
Privacy Masking	18 Zones Programmable
Motion Detection	On:sensitivity, programmable /Off
Lens Shading Compensation	On/Off
ENVIRONMENTAL	
Operation Temp./RH	-10°C~50°C / Less than RH80%
Protection Level.	IP66
ELECTRICAL	
Power Supply	12V DC, 12V DC/24V AC (PoC)
Power Consumption	7.2W, 8.2W (PoC)
MECHANICAL	
Dimensions	φ140x112mm
Net weight	1000g

* Derivative products : DSS-219RHV

Surveillance Series